


NEWGEN GUIDE AND CURTAIN LOK SYSTEM STEEL JAMB MOUNTING



NEWGEN GUIDE AND CURTAIN LOK SYSTEM CONCRETE WALL MOUNTING **

** CLEARANCE DIMENSION IS 8" FOR CONCRETE MOUNT CONFIGURATION
 *** IF 600V SUPPLY, THEN CONTROL PANEL (20"W x 24"H x 9.25"D)

TNR INDUSTRIAL DOORS INC.	
SHOP DRAWING, MODEL HDL45, LEFT HAND	
ECT. DETAIL: DIRECT DRIVE OPERATOR	
LIMITATIONS: [20" OW = 25' & 20" OR = 30'] OR [25" OW = 30' & OH = 20']	
DATE DRN: SEPT. 24, 2013	REVISION: E - JUNE 27, 2016
DRAWN BY: R.B.	DRAWING No.: D-600-0094
ELECTRICAL CRITERIA: PLC & FREQUENCY INVERTER DRIVE	
CONTROL PANEL NEMA/ESMAC 4 STD. OR _____	
PRIMARY POWER SUPPLY: _____ Volts, 3 Phase, 60 Hertz.	
OPERATOR CRITERIA: DIRECT DRIVE	
OPERATOR NEMA/ESMAC 4 STD. OR _____	
2.25 HP. DOOR SPEED: OPEN @ _____ ips, CLOSE @ _____ ips	
KND USER: _____	
DEALER: _____	
DOOR SIZE: _____	SERIAL No.: TNR- _____

MECHANICAL OPTIONS	ELECTRICAL OPTIONS	STANDARD SYSTEM INCLUDES
<input type="checkbox"/> - GUIDE MOUNTED WINDBAR	<input type="checkbox"/> - LOOP DETECTOR	- SPEEDS UP TO 24 IPS OPEN, 24 IPS CLOSE
<input type="checkbox"/> - JAMB MOUNTED WINDBAR	<input type="checkbox"/> - WIRELESS RECEIVER	- TIMER TO CLOSE (USER SELEC)
<input type="checkbox"/> - GUIDE GUARDS	<input type="checkbox"/> - WIRELESS TRANSMITTER, QTY. _____	- NEMA 4 CONTROL PANEL & OPERATOR
<input type="checkbox"/> - EXTERIOR HOODS	<input type="checkbox"/> - N 4X PUSHBUTTON STN, QTY. _____	- PROGRAMMABLE CONTROLLER
<input type="checkbox"/> - 16" x 16" WINDOWS, QTY. _____	<input type="checkbox"/> - MOTION DETECTOR, QTY. _____	- FREQUENCY INVERTER
<input type="checkbox"/> - BLUE EPDM CURTAIN	<input type="checkbox"/> - ADD. THRU-BEAM PHOTOEYE, QTY. _____	- AIR WAVE REVERSING EDGE c/w COIL CORD
<input type="checkbox"/> - GRAY EPDM CURTAIN	<input type="checkbox"/> - ADD. REFLECTIVE PHOTOEYE, QTY. _____	- 5" HIGH, BLACK EPDM RUBBER LOOP
<input type="checkbox"/>	<input type="checkbox"/> - ELECTRIC REVERSING EDGE	- KNOCK-AWAY STYLE BOTTOM BAR
<input type="checkbox"/>	<input type="checkbox"/> - WIRELESS AIR WAVE REVERSING EDGE	- NEWGEN GUIDE AND CURTAIN LOK SYSTEM
<input type="checkbox"/>	<input type="checkbox"/>	- THRU-BEAM PHOTOEYE
<input type="checkbox"/>	<input type="checkbox"/>	- ROTARY DISCONNECT
<input type="checkbox"/>	<input type="checkbox"/>	-